

Application No. 09/746,744
Filed: December 22, 2000
TC Art Unit: 2666
Confirmation No.: 6878

AMENDMENT TO THE CLAIMS

1. (Currently Amended) A method for switching data packet flows with guaranteed delay and bandwidth, comprising:

receiving expected packet arrival time information at a switch, wherein said expected packet arrival time information is associated with a packet flow, and wherein said expected packet arrival time information indicates an expected packet arrival time at which at least one packet associated with said packet flow is expected to be received by said switch ~~will receive a packet associated with a packet flow;~~

receiving forwarding information associated with said packet flow, wherein said forwarding information associated with said packet flow indicates ~~ing~~ how said switch should forward received ~~packets~~ a packet that arrives at said expected packet arrival time, associated with said packet flow and associating said forwarding information with said expected packet arrival time;

pre-establishing a path through said switch for a duration ~~predetermined period of a time slot~~ that includes said expected packet arrival time;

receiving said ~~a packet associated with said packet flow~~ at said expected packet arrival time; and

forwarding, via said pre-established path through said switch, said packet based on said forwarding information associated with said expected packet arrival time ~~in accordance with said forwarding information associated with said packet flow.~~

2. (Currently Amended) The method of claim 1, further comprising:

receiving packet transmission time information at said switch, wherein said packet transmission time information is associated with said packet flow, wherein said packet transmission time information indicates a packet transmission time at which said switch may transmit said packet associated with said packet flow; and

wherein said forwarding said packet ~~based on said packet arrival time~~ includes transmitting said packet at said packet transmission time.

Application No. 09/746,744
Filed: December 22, 2000
TC Art Unit: 2666
Confirmation No.: 6878

3. (Currently Amended) The method of claim 2, further comprising:
associating said expected packet arrival time information with a first port of said switch; and
wherein said receiving of said packet is at said first port of said switch.
4. (Original) The method of claim 3, further comprising:
associating said packet transmission time information with a second port of said switch; and
wherein said transmitting of said packet is at said second port of said switch.
5. (Original) The method of claim 4, further comprising:
wherein said packet flow is associated with a real-time application;
receiving another packet associated with a non-real-time application; and
delaying transmission of said non-real-time packet in order to perform said transmitting of
said packet associated with said real-time application.
6. (Original) The method of claim 5, wherein said receiving of said packet associated with said non-real-time application occurs prior to said receiving of said packet associated with said real-time application.
7. (Currently Amended) The method of claim 1, further comprising:
receiving a reference packet at a reference time;
determining a schedule interval start time in response to said reference time; and
determining said expected packet arrival time based on said expected packet arrival time
information and said schedule interval start time.
8. (Currently Amended) The method of claim 7, wherein said expected packet arrival time
information includes a packet flow offset value, and wherein said determining said expected packet
arrival time includes adding said packet flow offset value to said schedule interval start time.
9. (Original) The method of claim 2, further comprising:

Application No. 09/746,744
Filed: December 22, 2000
TC Art Unit: 2666
Confirmation No.: 6878

receiving a reference packet at a reference time;
determining a schedule interval start time in response to said reference time; and
determining said packet transmission time based on said packet transmission time information and said schedule interval start time.

10. (Original) The method of claim 9, wherein said packet transmission time information includes a packet flow offset value, and wherein said determining said packet transmission time includes adding said packet flow offset value to said schedule interval start time.

11. (Original) The method of claim 2, further comprising:

transmitting said packet transmission time information to a second switch; and
receiving acknowledgement of said packet transmission time information, wherein said acknowledgement of said packet transmission time information includes either approval or disapproval.

12. (Currently Amended) An apparatus for switching data packet flows with guaranteed delay and bandwidth, comprising:

control logic for receiving expected packet arrival time information at a switch, wherein said expected packet arrival time information is associated with a packet flow, and wherein said expected packet arrival time information indicates an expected packet arrival time at which at least one packet associated with said packet flow is expected to be received by said switch-will receive a packet associated with a packet flow;

control logic for receiving forwarding information associated with said packet flow, wherein said forwarding information ~~associated with said packet flow indicates~~ how said switch should forward received packets a packet that arrives at said expected packet arrival time, associated with said packet flow and associating said forwarding information with said expected packet arrival time;

control logic for pre-establishing a path through said switch for a duration of predetermined period of a time slot that includes said expected packet arrival time;

Application No. 09/746,744
Filed: December 22, 2000
TC Art Unit: 2666
Confirmation No.: 6878

control logic for receiving ~~said a packet associated with said packet flow at said expected~~
packet arrival time; and

control logic for forwarding, via said pre-established path through said switch, said packet
based on said forwarding information associated with said expected packet arrival time ~~in~~
~~accordance with said forwarding information associated with said packet flow.~~

13. (Currently Amended) The apparatus of claim 12, further comprising:

control logic for receiving packet transmission time information at said switch, wherein said
packet transmission time information is associated with said packet flow, wherein said packet
transmission time information indicates a packet transmission time at which said switch may
transmit said packet associated with said packet flow; and

wherein said control logic for forwarding said packet ~~based on said packet arrival time~~
includes control logic for transmitting said packet at said packet transmission time.

14. (Currently Amended) The apparatus of claim 13, further comprising:

control logic for associating said expected packet arrival time information with a first port of
said switch; and

wherein said control logic for receiving of said packet is associated with said first port of
said switch.

15. (Original) The apparatus of claim 14, further comprising:

control logic for associating said packet transmission time information with a second port of
said switch; and

wherein said control logic for transmitting said packet is associated with said second port of
said switch.

16. (Currently Amended) The apparatus of claim 15, ~~further comprising~~ wherein:

~~wherein~~ said packet flow is associated with a real-time application; and further comprising:

Application No. 09/746,744
Filed: December 22, 2000
TC Art Unit: 2666
Confirmation No.: 6878

control logic for delaying transmission of a received non-real-time packet in order to perform said transmitting of said packet associated with said real-time application.

17. (Original) The apparatus of claim 16, wherein said control logic for delaying said transmission of said received non-real-time packet is operable to delay said transmission of said received non-real-time packet in the event that said non-real-time packet is received prior to said receiving of said packet associated with said real-time application.

18. (Currently Amended) The apparatus of claim 12, further comprising:

control logic for ~~processing~~ receiving a reference packet at a reference time;

control logic for determining a schedule interval start time in response to said reference time; and

control logic for determining said expected packet arrival time based on said expected packet arrival time information and said schedule interval start time.

19. (Currently Amended) The apparatus of claim 18, wherein said expected packet arrival time information includes a packet flow offset value, and wherein said control logic for determining said expected packet arrival time includes control logic for adding said packet flow offset value to said schedule interval start time.

20. (Original) The apparatus of claim 13, further comprising:

control logic for receiving a reference packet and for recording a reference time at which said reference packet was received;

control logic for determining a schedule interval start time in response to said reference time; and

control logic for determining said packet transmission time based on said packet transmission time information and said schedule interval start time.

Application No. 09/746,744

Filed: December 22, 2000

TC Art Unit: 2666

Confirmation No.: 6878

21. (Original) The apparatus of claim 20, wherein said packet transmission time information includes a packet flow offset value, and wherein said control logic for determining said packet transmission time includes control logic for adding said packet flow offset value to said schedule interval start time.

22. (Original) The apparatus of claim 13, further comprising:

control logic for transmitting said packet transmission time information to a second switch;
and

control logic for receiving acknowledgement of said packet transmission time information, wherein said acknowledgement of said packet transmission time information includes either approval or disapproval.

23. (Currently Amended) A network of communication devices including a plurality of packet switching devices according to claim 13, and wherein a first subset of said plurality of switching devices are originators of reference packets including said expected packet arrival time information and said packet transmission time information, and a second subset of said plurality of packet switching devices are receivers of said reference packets including said expected packet arrival time information and said packet transmission time information.

24. (Currently Amended) A network of communication devices including a plurality of packet switching devices according to claim 13, and wherein a predetermined one of said plurality of switching devices operates as a centralized scheduling agent and originates reference packets including said expected packet arrival time information and said packet transmission time information.

25. (Currently Amended) A schedule-based packet switch, comprising:

a master clock system, said master clock system operative to determine a beginning of a schedule interval;

Application No. 09/746,744
Filed: December 22, 2000
TC Art Unit: 2666
Confirmation No.: 6878

schedule information defining at least one packet flow schedule, wherein said schedule information defines scheduled reception and transmission times for at least one packet associated with said at least one packet flow, wherein the scheduled reception time indicates an expected packet arrival time at which said at least one packet associated with said at least one packet flow is expected to be received by said switch; and

a plurality of interface ports, each of said interface ports having transmit control logic and receive control logic, wherein each of said transmit and receive ~~functions are~~ logic is responsive to said schedule information and said master clock system, wherein said transmit control logic of at least one of said plurality of interface ports is operable to determine a transmit time of a received packet associated with said at least one packet flow in response to a transmit time offset into said schedule interval defined by said packet flow schedule.

26. (Currently Amended) The schedule-based packet switch of claim 25, wherein said receive control logic of at least one of said plurality of interface ports is operable to determine an expected reception time of a packet associated with said at least one packet flow in response to a reception time offset into said schedule interval defined by said packet flow schedule.

27. (Previously Presented) The schedule-based packet switch of claim 25, wherein said master clock system is responsive to an external clock reference, wherein said external clock reference is based on a received heartbeat packet.

28. (Currently Amended) A method for schedule-based packet switching in a scheduled packet switch, comprising:

determining, by a master clock system in said scheduled packet switch, a beginning of a schedule interval;

storing, within said scheduled packet switch, schedule information defining at least one packet flow schedule, wherein said schedule information defines scheduled reception and transmission times for at least one packet associated with said at least one packet flow, wherein the scheduled reception time indicates an expected packet arrival time at which said at least one packet

Application No. 09/746,744
Filed: December 22, 2000
TC Art Unit: 2666
Confirmation No.: 6878

associated with said at least one packet flow is expected to be received by said scheduled packet switch; and

determining, at a transmit control logic of an interface port of said scheduled packet switch, and responsive to said schedule information and said master clock system, a transmit time of a received packet associated with said at least one packet flow in response to a transmit time offset into said schedule interval defined by said packet flow schedule.

29. (Currently Amended) The method of claim 28, further comprising determining, at a receive control logic of an interface port of said scheduled packet switch, and responsive to said schedule information and said master clock system, an expected reception time of a packet associated with said at least one packet flow in response to a reception time offset into said schedule interval defined by said packet flow schedule.

30. (Previously Presented) The method of claim 28, further comprising:

receiving a heartbeat packet; and

determining, by said master clock system in response to said heartbeat packet, said beginning of said schedule interval.

31. (New) The method of claim 1, wherein:

said pre-establishing said path through said switch comprises establishing said path from a first port of said switch to a second port of said switch, according to said forwarding information.

32. (New) The method of claim 31, further comprising:

after the predetermined period of time, disestablishing said path through said switch.

33. (New) The method of claim 31, further comprising:

periodically re-establishing said path, from said first port to said second port, through said switch, for said predetermined period of time; and

Application No. 09/746,744
Filed: December 22, 2000
TC Art Unit: 2666
Confirmation No.: 6878

forwarding any received packets received at said first port, while said path is established, by transmitting said any received packets at said second port, in accordance with said forwarding information associated with said packet flow.

34. (New) The method of claim 33, wherein:

said expected packet arrival time information further indicates a repeat time interval between packets that are associated with said packet flow and that are expected to be received by said switch; and

said periodically re-establishing said path comprises periodically re-establishing said path according to said repeat time interval.

35. (New) The method of claim 1, wherein:

said expected packet arrival time information further indicates a repeat time interval between packets that are associated with said packet flow and that are expected to be received by said switch; and further comprising:

receiving subsequent packets at times corresponding to said expected packet arrival time and said repeat time interval; and

forwarding said subsequent packets based on said forwarding information associated with said expected packet arrival time.

36. (New) The method of claim 1, wherein:

said forwarding said packets comprises forwarding said packet without referencing destination information with said packet.

37. (New) The apparatus of claim 12, wherein:

said control logic for pre-establishing said path through said switch comprises a crosspoint matrix communicably coupled to said control logic for receiving said packet and to said control logic for forwarding said packet and operable to establish said path, from a first port to a second port, through said switch, according to said forwarding information.

Application No. 09/746,744

Filed: December 22, 2000

TC Art Unit: 2666

Confirmation No.: 6878

38. (New) A network of communication devices including a plurality of packet switching devices according to claim 13, further comprising a centralized scheduling agent that originates reference packets including said expected packet arrival time information and said packet transmission time information.

39. (New) A method for switching data packet flows with guaranteed delay and bandwidth, comprising:

receiving expected packet arrival time information at a switch, wherein said expected packet arrival time information is associated with a packet flow, and wherein said expected packet arrival time information indicates an expected packet arrival time at which at least one packet associated with said packet flow is expected to be received by said switch;

receiving forwarding information associated with said packet flow, wherein said forwarding information indicates how said switch should forward a packet that arrives at said expected packet arrival time, and associating said forwarding information with said expected packet arrival time;

pre-establishing a path through said switch for a predetermined amount of time, based on said expected packet arrival time;

receiving a packet during said predetermined amount of time; and

forwarding, via said pre-established path through said switch, said packet based on said forwarding information associated with said expected packet arrival time.

40. (New) The method of claim 39, further comprising:

receiving packet transmission time information at said switch, wherein said packet transmission time information is associated with said packet flow, wherein said packet transmission time information indicates a packet transmission time at which said switch may transmit said packet associated with said packet flow; and

wherein said forwarding said packet includes transmitting said packet at said packet transmission time.

Application No. 09/746,744
Filed: December 22, 2000
TC Art Unit: 2666
Confirmation No.: 6878

41. (New) The method of claim 39, wherein:

said pre-establishing said path through said switch comprises establishing said path from a first port of said switch to a second port of said switch, according to said forwarding information.

42. (New) The method of claim 41, further comprising:

periodically re-establishing said path, from said first port to said second port, through said switch, for said predetermined period of time; and

forwarding any received packets received at said first port, while said path is established, by transmitting said any received packets at said second port, in accordance with said forwarding information associated with said packet flow.

43. (New) The method of claim 42, wherein:

said expected packet arrival time information further indicates a repeat time interval between packets that are associated with said packet flow and that are expected to be received by said switch; and

said periodically re-establishing said path comprises periodically re-establishing said path according to said repeat time interval,

44. (New) The method of claim 39, wherein:

said forwarding said packet comprises forwarding said packet without referencing destination information within said packet.